

FLYCASE PRO

EXTERNAL STORAGE PERIPHERALS RAID 0*



FIREWIRE A (400) & B (800)

MAC & PC

Ultra-fast FireWire 400 & 800.

Storage capacities up to 800 GB**.

Installs in seconds.

"Plug and Play" and Hot-pluggable.

Integrate any standard 3.5" 7200 RPM high-performance ATA hard disk drives.

Standard interfacing compatible SBP2/IEEE-1394A and B with host computer.

Backup, partition and format your drive using the step-by-step software package, includes automatic backup feature.

Built in fan for an excellent airflow.

Compact aluminium case, designed for professional content.

Supports multi-stream video playback with real-time effects on final Cut Pro HD, Premiere Pro and others.

TECHNICAL SPECIFICATIONS

Capacities	400, 500, 600, 800 GB
Transfer rate	up to 800 Mbits/s
Transfer rate FireWire 800	Up to 88 MB/s
Dimensions	230 x 150 x 65 mm
Maximum power consumption	15 W
Power supply adapter	12 V/5V (15 W)
Weight	1770 g

(*) Connection (high performance) of two hard disk drives.

(**) The maximum capacity available may vary according to the availability of 3.5" hard disk drives in the market. When in use the capacity available will depend on the operating system installed.

MINIMUM REQUIREMENTS

- Intel Pentium II 350 MHz-compatible or Apple G3 processor and higher
- Computer equipped with FireWire 400 (6-pin) or (4-pin), MAC OS 9.x and MAC OS 10.x, Windows 2000 and Windows XP
- Computer equipped with FireWire 800 (9-pin), MAC OS 10.2.4 and higher (Apple G4 processor required), Windows 2000 and Windows XP

PACKAGE CONTAINS

- 1 Flycase PRO
- 1 FireWire 800 (9-to-9 pin) cable
- 1 FireWire 400 (6-to-6 pin) cable
- 1 FireWire iLink/DV (6-to-4 pin) cable
- 1 External AC/DC power supply (UK or Europe)
- 1 CD containing User's guide, Drivers and Software,
- 1 Quick installation guide

© PikaOne 2004. All rights reserved.

Any reproduction, even partial, of this datasheet, in whatever form, without written authorization from PikaOne is strictly prohibited and is a violation of Copyright

**Pika
ONE**

www.pikaone.com